














The Florida Department of Community Affairs Building Code Information System

SITE NAVIGATION

-  Home
-  Course Accreditation
-  Florida Building Code
-  Manufact. Buildings
-  Prototype Building
-  Surcharges
-  Training
-  Product Approval
-  License Search
-  Mailing List
-  Florida Building Commission

PRODUCT APPROVAL

Product Type Detail

- Overview
- Product Search
- Organization Search
- Product Application

User: Public User - Not Associated with Organization -

[Need Help ?](#)

Application #: FL4931
 Date Submitted: 07/29/2005
 Code Version: 2004

Product Manufacturer: Watkins Sawmills Ltd
 Address/Phone/email: 9414 288th St.
 Mission, british columbia v2t5w4
 (604) 462-7116

Category: Roofing

Subcategory: Wood Shingles and Shakes

Evaluation Method: Certification Mark or Listing

Referenced Standards from the Florida Building Code:

Section	Standard	Year
	CSSB	1997
	TAS 100	1995

Certification Agency: Miami-Dade BCCO - CER

Quality Assurance Entity:

Validation Entity:

Authorized Signature: troy welsh
 sales@watkinsawmills.com

Evaluation/Test Reports Uploaded:

Installation Documents Uploaded:

Product Approval Method: Method 1 Option A

Application Status: Pending FBC Approval
 Date Validated: 07/29/2005
 Date Approved:

Date Certified to the 2004 Code:

Page:

Page 1 / 1

App/Seq #	Product Model # or Name	Model Description	Limits of Use
4931.1	Cedar shakes widths 4" to 11", lengths 15", 18", and 24"	Tapered or non-tapered, may be preservative or fire retardant treated, cedar shakes graded and certified to CSSB 1995 Standards.	1. Can be used in HVHZ per NOA #02-0919.02. 2. This acceptance is for wood deck application. Minimum deck requirements shall be in compliance with applicable Building Code. 3. Wood shakes shall not be installed on roof mean heights greater than 33 ft.
4931.2	Cedar shingles widths 4' to 11", lengths 16", 18".	May be preservative or fire retardant treated cedar shingles graded and certified to CSSB 1995 Standards	1. Can be used in HVHZ per NOA #02-0919.02. 2. This acceptance is for wood deck application. Minimum deck requirements shall be in compliance with applicable Building Code. 3. Wood shingles shall not be installed on roof mean heights greater than 33 ft.



Copyright and Disclaimer ; ©2000 The State of Florida. All rights reserved.