



**Product Approval**  
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

OFFICE OF THE  
SECRETARY

FL #	FL13714-R4						
Application Type	Revision						
Code Version	2017						
Application Status	Approved						
	*Approved by DBPR. Approvals by DBPR shall be reviewed and ratified by the POC and/or the Commission if necessary.						
Comments							
Archived	<input type="checkbox"/>						
Product Manufacturer	Watkins Sawmills Ltd						
Address/Phone/Email	9414 288th St. Mission, NON-US 00000 (604) 462-7116 troy@watkinsawmills.com						
Authorized Signature	Troy Welsh troy@watkinsawmills.com						
Technical Representative							
Address/Phone/Email							
Quality Assurance Representative							
Address/Phone/Email							
Category	Roofing						
Subcategory	Wood Shingles and Shakes						
Compliance Method	Certification Mark or Listing						
Certification Agency	Miami-Dade BCCO - CER						
Validated By	Chris Bowness, P.E. <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received						
Referenced Standard and Year (of Standard)	<table border="0"> <thead> <tr> <th><u>Standard</u></th> <th><u>Year</u></th> </tr> </thead> <tbody> <tr> <td>CSSB</td> <td>1997</td> </tr> <tr> <td>TAS 100</td> <td>1995</td> </tr> </tbody> </table>	<u>Standard</u>	<u>Year</u>	CSSB	1997	TAS 100	1995
<u>Standard</u>	<u>Year</u>						
CSSB	1997						
TAS 100	1995						
Equivalence of Product Standards Certified By	Approved Certification Agency <a href="#">FL13714_R4_Equiv_New_NOA_.pdf</a>						
Product Approval Method	Method 1 Option A						
Date Submitted	03/06/2018						
Date Validated	04/04/2018						
Date Pending FBC Approval							

**Summary of Products**

FL #	Model, Number or Name	Description
13714.1	Cedar Shakes widths 4" to 11", lengths 15", 18", 24"	Tapered or Non-Tapered, may be preservative or Fire retardant Treated, Cedar Shakes graded and certified to the CSSB 1997 Standards.
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> 1. Can be used in HVHZ per NOA # 17-1211.09 This acceptance is for wood deck application. Minimum deck requirements shall be in compliance with applicable Building Code. 3. Wood shingles shall not be installed on roof mean heights greater than 33 ft.		<b>Certification Agency Certificate</b> <a href="#">FL13714_R4_C_CAC_NOA_17-1211.09.pdf</a> <b>Quality Assurance Contract Expiration Date</b> 02/20/2023 <b>Installation Instructions</b> <a href="#">FL13714_R4_II_NOA_17-1211.09.pdf</a> Verified By: Miami-Dade BCCO - CER Created by Independent Third Party: <b>Evaluation Reports</b> Created by Independent Third Party:
13714.2	Cedar Shingles widths 4" to 11", lengths 16", 18"	Tapered, may be preservative or Fire retardant Treated, Cedar Shingles graded and certified to the CSSB 1997 Standards.
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> 1. Can be used in HVHZ per NOA # 17-1211.09 This acceptance is for wood deck application. Minimum deck requirements shall be in compliance with applicable Building Code. 3. Wood shingles shall not be installed on roof mean heights greater than 33 ft.		<b>Certification Agency Certificate</b> <a href="#">FL13714_R4_C_CAC_NOA_17-1211.09.pdf</a> <b>Quality Assurance Contract Expiration Date</b> 02/20/2023 <b>Installation Instructions</b> <a href="#">FL13714_R4_II_NOA_17-1211.09.pdf</a> Verified By: Miami-Dade BCCO - CER Created by Independent Third Party: <b>Evaluation Reports</b> Created by Independent Third Party: